




Flat Top Fencing Rail Galvanised



AUTOPA's Flat Top Fencing Rail is ideal for marking paths and securing perimeters at residential and commercial properties. All the products in the range are manufactured by AUTOPA from mild steel which is galvanised for longevity. The fence panels are supplied galvanised as standard and can be colour coated if required. RAL numbers must be specified at time of order.

The infill bars are manufactured from 12mm diameter mild steel, spaced 100mm apart. AUTOPA's Flat Top fencing rail is available 1000mm or 1200mm above ground with a choice of panel widths.

All panels and posts are supplied with the appropriate brackets and fixings for ease of install.



Part Number	Description	Weight (kg)
138 174 650	18 Bar Panel, 1000mm Tall - Galvanised	22kg
138 174 655	18 Bar Panel, 1200mm Tall - Galvanised	25kg
138 174 675	24 Bar Panel, 1000mm Tall - Galvanised	29kg
138 174 666	24 Bar Panel, 1200mm Tall - Galvanised	33kg
138 501 800	Rail Post, 1000mm Tall - Galvanised	7kg
138 501 802	Rail Post, 1200mm Tall - Galvanised	8kg

Product details

- 12mm diameter bar
- 18 bar panel - 1800mm wide
- 24 bar panel - 2400mm wide
- Each fence panel requires a fence stay which is 200mm below ground
- Available either 1000mm or 1200mm height above ground
- Concrete in 500mm/550mm (below ground) - Rail posts only

Installation & use

1000mm tall rail posts require a hole of at least 500mm for casting into concrete.

1200mm tall rail posts require a hole of at least 550mm for casting into concrete.

This product is guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk
+44 (0)1788 550556

AUTOPA Limited
Cottage Leap, Rugby, Warwickshire CV21 3XP

