


## Hooped Perimeter Barrier with Horizontal Rail 48mm Diameter Galvanised, Concrete In





Perimeter Barriers are designed to help secure site perimeters and provide a permanent obstacle to vehicle access, to mark boundaries, define trolley parks and protect vulnerable door entrances and exits.

Suited to sites where aesthetics and security are equally important, perimeter barriers are commonly found outside car showrooms acting as protection for the cars on the forecourt without impeding a customer's view of the vehicles.

Available in a variety of heights and widths, available as concrete in, bolt down or removable for occasional access.

Available as galvanised as standard. Stainless steel, galvanised and colour coated available extra.



Part Number	Description, Height above ground x overall width	<u>Weight (kg)</u>
138 174 842	500 x 500 with Horizontal Rail, Galvanised - Concrete In	7kg
138 174 841	500 x 1000 with Horizontal Rail, Galvanised - Concrete In	10kg
138 174 840	500 x 1500 with Horizontal Rail, Galvanised - Concrete In	14kg
138 174 839	500 x 2000 with Horizontal Rail, Galvanised - Concrete In	17kg
138 174 851H	750 x 1000 with Horizontal Rail, Galvanised - Concrete In	12kg
138 174 858	750 x 1500 with Horizontal Rail, Galvanised - Concrete In	16kg
138 174 862	750 x 2000 with Horizontal Rail, Galvanised - Concrete In	18kg
138 174 871	1000 x 1000 with Horizontal Rail, Galvanised - Concrete In	14kg
138 174 872	1000 x 1500 with Horizontal Rail, Galvanised - Concrete In	17kg
138 174 845	1000 x 2000 with Horizontal Rail, Galvanised - Concrete In	20kg

## **Product details**

- · 3mm wall thickness
- Concrete in 300mm (below ground)
- Colour coated options available extra

Complete with horizontal rail

Installation & use

Bolt down to a suitable concrete surface.

Telescopic, removable and concrete in are supplied with welded fixing spikes to ensure firm ground anchorage into concrete.

Telescopic, removable and concrete in require a suitable excavated hole for installing into concrete.

Products are guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk +44 (0)1788 550556

